

Can be installed to manage various torque tools with a small detector.

WDISR-IPS series

Built-in battery type. Successor model of DIS-IPS series



It works with a personal computer or PLC to manage torque measurement more highly. For managing automatic and semi-automatic tools.

A color display that can display various information.

Data output is standard equipment for both USB and RS232C.

Numerical values such as pass / fail conditions can be set up to 10 channels.

The pass / fail judgment is displayed in color for easy understanding.

Built-in battery drive.





●Color display that can display various information.



●Data output is standard equipment for both USB and RS232C.



●Setting various measurement parameters



A type that can be disengaged from high speed with a clutch at once

Use OW joint



Screw tightening robot etc.

A type that slowly re-tightens with current control

Use screw cube



Works with "PC" and "PLC"

Various commands can be input from PLC or personal computer. Finer torque management is possible with external control.



Command list

Clear signal: Clears the display and outputs the held numerical value as data and saves it in memory.

Measurement mode: Change the measurement mode.

Measurement channel: Change individual channels for which conditions such as pass / fail judgment are set.

Peak hold upper limit : Change the pass / fail judgment upper limit of the current channel.

Peak hold lower limit: Change the pass / fail judgment lower limit of the current channel.

Peak down lower limit: Change the peak down judgment start lower limit of the current channel.

Real-time output lower limit: Changed the output lower limit of real-time output.

Auto clear time: Changed the time to automatically clear after the measurement is completed.

Buzzer notification: Changed the buzzer notification method.

Specification

Model	WDISR-IPS05C		WDISR-IPS5C	WDISR-IPS20CL
Applications	It is a torque measuring equipment to measure the tightening torque of tightening tools (electric screwdriver, torque screwdriver, etc.) in screw tightening work.			
Power supply	Internal battery (12 hours continuous operation time, 3 hours charging time)			
Rate input voltage	12V DC			
Measurement range	2.0 ~ 500.0 [mN-m]		0.020 ~ 5.000 [N-m]	0.20 ~ 20.00 [N-m]
Measurement Unit	kgf-cm / lbf-in / mN-m / cN-m		kgf-cm / lbf-in / N-m / cN-m	
Accuracy	±0.5% (If 499 digit or less, ±3 digit.)			
Sampling rate	1000 data / 1sec			
Measurement mode	Measurement mode		Data output	Contents
	Peak hold	PP	○	Measure the peak torque.
	Peak down	PD	○	Measure the first peak torque.
	Real time output	C	○	The data output cycle is approximately 180 data / 1 second.
	Track	TR	—	Mainly used for calibration.
	If the measurement mode is TR, the data isn't outputted.			
Data output	Wired (ASCII format)			
Memory size	800 data			
Auto power off	Power off after 10 minutes of non-use			
Accessories, Attachments	Detector (Refer below)			
	Detector cable			
	Joint OW-025		Joint OW-10	Joint OW-20
	Cube (H20×W20×D20)			
	SC-1 with the screw hole of M1, M1.2, M1.4, M2 and M3		SC-2 with the screw hole of M2.6, M3, M4, M5 and M6	SC-3 with the screw hole of M4, M5, M6, M8 and M10
	AC adaptor			
	Rubber feet			
	Result of calibration, Certification on calibration, Traceability system figure			

Detector

Model	IPS05C / 5C	IPS20CL
Shapes (Unit: mm)		
Socket	□20mm	

