PosiTector[®] SPG Series

Surface Profile Gages for blasted steel and textured coatings







PosiTector SPG Series

All Gages Feature...

Simple

- Fast measurement rate of over 50 readings per minute ideal for quickly and accurately measuring large surface areas
- Enhanced one-handed menu navigation
- RESET feature instantly restores factory settings

Durable

NEW! Alumina wear face and tungsten carbide tip for long life and continuous accuracy—field replaceable tips

- Solvent, acid, oil, water and dust resistant—weatherproof
- Rugged, indoor/outdoor instrument—ideal for field or shop use
- Shock-absorbing, protective rubber holster with belt clip
- Two year warranty on body and probe

Accurate

- Built-in temperature compensation ensures measurement accuracy
- Certificate of Calibration showing traceability to PTB included
- Glass zero plate and metal shim included
- Conforms to national and international standards

Versatile

- PosiTector body accepts ALL PosiTector SPG, RTR, 6000, 200, DPM, and UTG probes easily converting from a surface profile gage to a coating thickness gage, dew point meter or wall thickness gage
- NEW! Separate probes available for blasted steel and textured coatings
 - 30° angle probe tips available for special applications
 - Selectable display languages
 - High contrast backlit display for bright or dark environments
 - Flip display enables right-side-up viewing
 - Uses alkaline or rechargeable batteries (built-in charger)

Powerful

- Continually displays/updates average, standard deviation, min/max depth and number of readings
- HiLo alarm audibly and visibly alerts when measurements exceed specified limits
- Every stored measurement is date and time stamped
- Screen capture—save screen images into memory for record keeping
- USB port for fast, simple connection to a PC and to supply continuous power. USB cable included
- PosiSoft USB Drive—stored readings and graphs can be accessed using universal PC/Mac web browsers or file explorers. No software required
- Software updates via the internet keep your gage current
- Includes PosiSoft Suite of solutions for analyzing and reporting data

Ordering Guide

Probe Type		Built-in	Cabled		
Standard		SPG 1	SPG S1	SPG CS1	
Advanced		SPG 3	SPG S3	SPG CS3	
Range		0–500 μm 0–20 mils		0−1,500 µm 0−60 mils	
Accuracy					
Тір	Angle	60°*		60°	
	Radius	50 µm (2 mils)		500 µm (20 mils)	

*30° tips available for conforming to Austrailian standard AS 3894.5-C

Standard Models

Includes ALL features as shown on left plus...

- High contrast reversible color LCD
- Storage of 250 readings—stored readings can be viewed or downloaded

Advanced Models

Includes ALL features as shown on left plus...

- High contrast reversible color LCD
- Storage of 100,000 readings in up to 1,000 batches and sub-batches
- SmartBatchTM allows entry of user-defined parameters and criteria to comply with various standards and test methods
- WiFi technology—wirelessly synchronizes with PosiSoft.net, downloads software updates and connects to mobile devices for expanded functionality
- Bluetooth Wireless Technology for data transfer to a computer or optional portable printer
- Real time graphing, picture prompting and batch notes
- Onscreen Batch Annotation—add notes, change batch names and more with built-in QWERTY keyboard

NEW PosiTector SmartLink Compatible

- Wirelessly connect PosiTector SPG probes to your smart device
- Turns your cell phone or tablet into a virtual PosiTector gage



NEW! All probes feature a durable Alumina wear face and tungsten carbide tip for long life and continuous accuracy.

Accessories

- Certified SPG Standards to verify accuracy and operation of surface profile depth micrometers
- Replacement non-certified metal check shim and glass zero plate
- Replacement tungsten carbide probe tips
- AC Power Kit for continuous AC operation or battery charging
- Rechargeable Batteries—a set of eneloop NiMH AAA batteries

All Gages Come Complete with glass zero plate, metal check-shim, protective rubber holster with belt clip, wrist strap, 3 AAA batteries, instructions, nylon carrying case with shoulder strap, protective lens shield, Long Form Certificate of Calibration traceable to PTB, USB cable, two (2) year warranty.

Size: 137 x 61 x 28 mm (5.4" x 2.4" x 1.1") Weight: 140g (4.9 oz.) without batteries

Conforms to ASTM D4417-B, AS 3894.5-C (with optional 30° tip angle), U.S. Navy NSI 009-32, SANS 5772 and others


PosiSoft® Suite of Software

3 FREE ways to view and report your data

PosiSoft Desktop Software (v 4)

Powerful desktop software (PC/Mac) for downloading, viewing, printing and storing measurement data. Includes customizable, templated PDF Report Generator. No internet connection required.


- Import readings directly from the gage via USB
- Jobs feature consolidates and organizes batches and reports
- Export all data, settings and templates for backup and sharing



Generate Custom, Professional PDF Reports

Include inspection information such as on-site pictures, screen captures,

- notes and more to communicate important details Create and save multiple custom
- layouts as templates insert cover pages, add logos/images, and select font and point size
- Select the information to include for each product type – charts, histograms, readings, time stamps and more
- Compile multi-batch reports from one or more instrument types



PosiSoft.net

A web-based application offering secure centralized management of readings. Access your data from any web-connected device.

- Synchronize measurement data when connected via USB, Bluetooth or WiFi wireless technology
- Securely store measurement data in the cloud and share with authorized users via a secure login
- Generate reports with graphs, annotations and images



A simple interface to retrieve data from your gage in a manner similar to a USB flash drive. No software required.

 Measurement data can be printed quickly from an HTML report or exported in .CSV format for further analysis in *Excel*



osiTe	ctor	
atch B1		
1 Informa	tion	
Despective Tage follo Insta Type Prote follo (ac)	2012-01-2	5 106 146 211 75 26,00 8 23 00042 7 06 8
1 Summa		
-	7.00 5.0	i at at
1 Reading	is .	
1	2.500	
	6.2 mm	104 10 20
		104: 14: 41
	7.3 mile	104.36.43
	7.2 million	10.10.41
		64.14.17
	A. A. (1970)	
	2.4 mm	54 54 57
2		
-	8.4 mm	84 54.59 14 15 15 04 11 12
	8.4 mm	54 54,59 (14 15 1)
	R.4 min R.T.min R.S.min	14 54,50 14 15 15 14 15 15 14 15 15 14 15 15 14 15 15
1	5.4 min 5.7 min 5.4 min 5.4 min 5.2 min	144 544,50 144 195 195 144 195 195 144 195 195 144 195 195 144 195 195
11 12 12	8.4 min 8.1 min 8.2 min 8.2 min 8.3 min 1.3 min 7.3 min	64 54.50 64 15 55 64 15 55 64 15 55 64 15 55 64 15 55 64 15 55
# # 11 12 13	8.4 min 8.7 min 8.2 min 8.2 min 8.3 min 7.3 min 7.3 min	54 54.50 104 17 15 04 21 25 104 17 15 104 17 10 64 25 25 104 17 15 104 17 15
8 11 13 13 14 15 15	8.4 min 8.7 min 8.2 min 8.2 min 8.3 min 7.4 min 7.3 min 7.3 min	14,54,50 (4,11,12) (4,11,12) (4,11,12) (4,11,13) (4,11,13) (4,11,13) (4,11,13) (4,11,13) (4,11,13)
* 11 12 13 13	8.4 min 8.7 min 8.2 min 8.2 min 8.3 min 7.3 min 7.3 min	54 54.50 104 17 15 04 21 25 104 17 15 104 17 10 64 25 25 104 17 15 104 17 15

Learn more at <u>www.DeFelsko.com/PosiSoft</u>

	PosiSoft Desktop	PosiSoft.net	PosiSoft USB Drive
Generate basic, pre-formatted reports	•	•	•
Generate professional PDF reports with custom formatting. Add pictures, logos, screen captures, notes and more.	•	•	
Export to .CSV (comma separated values)	•	•	•
View and print readings stored on a PosiTector/PosiTest AT-A	•	•	•
Add photos and notes to reading data	•	•	
Software installation required	•		
Internet connection required		•	
Default download location for batches and readings	Hard Drive	Cloud	Gage
Multi-language support: English, Spanish, German, French, Chinese and Korean	•	•	★*
PC/Mac compatible	•	•	•
FREE	•	•	•
Compatible with all current PosiTector 6000/200/SPG/RTR/DPM/UTG and PosiTest AT series	•	•	◆ †

*PosiSoft USB Drive supports all 15 languages supported by the PosiTector gage. † PosiTest AT-M is not supported by PosiTector USB Drive

ELECTROMATIC Equip't Co., Inc., 600 Oakland Ave, Cedarhurst, New York 11516 - USA **Tel**: 800-645-4330 / 516-295-4300 **Fax**: 516-295-4399 **Web**: CheckLine.com **Email**: info@CheckLine.com