

ELAN EL-600-IC-8

ELAN<sup>®</sup>

# 600 Series In-Ceiling Speakers

(Sold In Pairs)



## Enhanced Performance.

A multipurpose speaker with step-up performance and a room-filling sound, the EL-600-IC-8 includes an upgraded injection molded Polypropylene cone woofer and pivoting 1" silk dome tweeter that's perfect for distributed audio or home theater.



# EL-600-IC-8 In-Ceiling Speakers

ORDER NO. EL-600-IC-8

# 600 SERIES

## ▪ Room Filling Sound

Low crossover points and a woofer that's mounted as close to the surface as possible delivers the widest dispersion and best sound quality possible.

## ▪ Silky Smooth Highs

Silk dome tweeters reduce the severity of break-up modes resulting in silky smooth sound which is pleasing to the ear—even at high volumes.

## ▪ Tilt Tweeter

The tilting tweeter mechanism allows you to direct sound to the listening area and maintains high frequency performance even when the speaker is mounted in less than ideal locations.

## ▪ Thin is In

A thin-bezel magnetic grille ensures a secure fit, pleasing aesthetic and with a one-step paint process, it fits universally into almost any décor.

## ▪ Easy-Grip Tweeter Bridge

We know you do it! Installing speakers above your head requires a sturdy grip point and the ELAN Tweeter bridge ensures you have one. We even protect the tweeter from accidental finger pokes.

## ▪ Dimpled Baffle Design

The dimpled baffle design eliminates annoying echoes and increases dispersion by reducing the focusing action of the concave baffle. The result is crystal-clear room-filling sound.

## ▪ Secure Connection

All ELAN speakers feature spring loaded binding posts that provide a secure, worry-free connection in the wall or ceiling.

## ▪ Lifetime Warranty

Feel confident that all ELAN architectural speakers are backed by a limited lifetime warranty.

SPECIFICATIONS	
Woofer Size	8" (200 mm)
Woofer Construction	Injection Molded Polypropylene Cone
Tweeter	1" (25 mm) Pivoting Silk Dome
Frequency Response	49Hz-20kHz
Impedance	8 Ohms
Power Handling	120 Watts
Sensitivity	90 dB
Timbre	Timbre-Matched to all 600 Series Speakers
Dimensions	10.8" (275 mm) Width x 4.4" (111 mm) Depth
Hole Cutout Dimensions	9.75" (248 mm) Diameter
Mounting Depth	4.25" (108 mm)



Use Pre-Construction Bracket  
EL-PCB-IC-8



**ELAN**<sup>®</sup>  
Your world, made simple.™

[www.elanhomesystems.com](http://www.elanhomesystems.com)