

IP Outdoor Fixed Lens Turret Camera with IR





High Performance Versatility.

The ELAN EL-IP-OTF2-WH is a versatile performer for installs requiring an outdoor/indoor camera that delivers crystal clear images, IP66 weather resistance, and superior IR captures in an elegant, attractive housing.

The EL-IP-OTF2-WH turret camera has a flat lens, independent IR sensor, for distortion-free images and superior IR capture with no IR bounce.

The EL-IP-OTF2-WH turret camera is quick and easy to install, and has great flexibility in terms of placement compared to dome cameras—it can be either ceiling mounted or wall mounted.

ELAN Discovery

Like all other ELAN Surveillance products, the ELAN EL-IP-OTF2-WH is embedded with the ELAN beacon, making it effortless to install in an ELAN system. In the Configurator, ELAN Discovery scans your network, both wired and wireless, automatically discovering the SSIDs of available devices. With a click, the camera is configured and installed in the ELAN system. We've eliminated the need to use a secondary application to setup the device outside of ELAN– saving you substantial time on every surveillance installation.

The EL-IP-OTF2-WH has the quality, reliability, best-in-class features and ELAN customer support that you and your clients rely on.

Comprehensive Surveillance

ELAN Surveillance cameras work seamlessly with the ELAN Network Video Recorder (EL-NVR Series) to create a surveillance ecosystem that excels in every application.



ELAN surveillance cameras feature oneclick camera setup with ELAN Discovery.



Illumination from Infrared (IR) LEDs enables night vision up to 30 meters.



Motion in front of the camera will be detected and saved as an event.



Back Light Compensation (BLC) adjusts the exposure of the image to properly expose the subject of interest.



Wide Dynamic Range improves image quality by balancing dark and light areas in an image.



EL-IP-OTF2-WH IP Outdoor Fixed Lens Turret Camera with IR



ORDER NO. EL-IP-OTF2-WH



FEATURES

- Auto-Discover/Auto-Configure
- 2 Megapixel
- 30m IR Distance
- 4mm Fixed Lens
- Advanced Built-in Motion Analytics
- IP66 Weather Resistant
- Alarm In/Out
- 2-Way Audio Support
- Automatic Gain Control (AGC)
- Operating Temperature: -40°F 122°F
- Max Frame Rate: 15FPS @ 1920x1080
- 3D Digital Noise Reduction
- 2D Wide Dynamic Range
- Power Over Ethernet (PoE)

INCLUDED IN THE BOX:

- (1) Camera
- (1) Quick Installation Guide
- (1) Mounting Template
- (3) Mounting Hardware
- (1) Allen Wrench

SPECIFICATIONS	
Power Consumption	DC12V - 5.8W / PoE - 7W (IEEE 802.3af)
Dimensions	4.5" x 3.6"
Weight	15.9 oz
Operating Temperature	-40°F - +122°F (-40°C - +50°C)
Angle of View	94°(H), 50°(V), 102°(D)
IR Range	30m
Alarm Event Triggers	Motion/Tamper/Network lost detection
Alarm Event Actions	FTP, SMTP, HTTP post, SD card, SAMBA
CPU Memory	Embedded SoC ARM Cortex-A9, 600MHz, 256MB DDR3, 256MB flash memory
Certifications	CE: Class B, FCC: Class B, IP66 Weather Resistant

VIDEO	
Video compression	Smart H.264/ H.264 High/Main Profile, Motion JPEG
Maximum Frame Rate	H.264 and MJPEG: : up to 30 FPS @ 1920 x 1080
Day/Night (IR-cut filter)	Color (Day), Monochrome (Night), Auto, Schedule
Scanning system	Progressive scan
Back Light Compensation	On / Off
2D WDR	Off / Auto / x2 / x3 / x4
3D Noise Reduction	Off / 1 to 32 selectable
Privacy Masking	Off / On (4 independent areas)
Sense Up	Off / 1 frame / 2 frames
Sense Up+	Yes
Auto Gain Control	36 dB variable gain
Other Functions	Sharpness, Hue, Image flip, Image mirror

NETWORK	
Ethernet	10Base-T / 100Base-TX, RJ-45
On-Screen Display (OSD)	Text over date, time, and camera name
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, MQTT, QoS, SNMP , SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, SDDP, Bonjour
Multi IP Addresses	Yes



Your world, made simple."

elancontrolsystems.com