geratech®







Features

- Displays N-m, Kg-cm, in-lb and ft-lb units (User selectable)
- CW and CCW operation
- Programmable Target Set-point with audible and LED indicators
- Peak or Real-Time (track) mode (User Selectable)
- At 90% of Target, Green LED illuminates with slow audible beep
- At 100% of Target, Green & Red LEDs illuminate with continuous beep
- Ratcheting Head





Model	Measuring Range	Resolution	Drive Size
DTWM-6	0.3 - 6 Nm	0.01 Nm	1/4''
DTWM-12	0.6 - 12 Nm	0.01 Nm	1/4''
DTWM-20	1 - 20 Nm	0.1 Nm	1/4''

Specifications	
Accuracy	CW ±2% / CCW ±3% of indicated from 20 - 100% of capacity
Operation Mode	Peak hold/ Track
Unit Selection	ft-lb, in-lb, N-m,
Length	8 inches / 20 mm
Head Type	Lever type Ratchet
Battery	1 AAA
Battery Life	12 Continuous Hours 1 Year Standby
Operating Temperature	-10°C ~ 60°C
Zero Function	To zero the DTL-100i press the "C" key. The display will clear then it will return to the "target value" (preset)
Storage Temperature	-20°C ~ 70°C
Humidity	Up to 90% non-condensing

DTW Series	
DTWA	Digital Torque Wrench - with Angle
DTWB	Digital Torque Wrench - Bicylcle Set
DTWI	Digital Torque Wrench - Interchangeable Head
DTWM	Digital Torque Wrench - Mini
DTWR	Digital Torque Wrench - Lever Type Ratchet

<u>geratech</u>[®]



www.geratech.com.tr www.egerate.com www.egerate-store.com