



E-DRIV[®] LF-Series

Brushless Electric Torque Screwdrivers

- Various models that range from 0.8 - 15.6 lbf.in
- High performance Swiss Maxon brushless motor design provides durability and reduces the standard maintenance costs for electric screwdrivers.
- Designed for high production environments. Minimal heat build-up even when tool is operated continuously.
- Over Heat Protection (OHP) and Over Current Protection (OCP) protect driver from damage or malfunction. Features a LED display that signals the tool status for the operator to view.
- Can be connected with the Scout Screw Counter.
- External torque adjustment scale.
- Requires STC 40 transformer (power supply).
- All models are ESD designed and prevent the occurrence of electro static discharge, which improves production yields, manufacturing costs, product quality, product reliability, reputation and profitability.



RoHS


Torque Cover: Item # 145823

Protects the LF-Series tools from incidental or operator tampering of torque setting.

Model	Driver Type	Item #	Torque Ranges		RPM	Grip Dia.	Length	Drive Size	Wt.	Applicable Screw Size
			lbf.in	cN.m						
LF060-A ESD	Lever Start	145897	0.8 - 5.2	3 - 58.8	1550	1 1/2"	9"	1/4 F/Hex	15.5 oz	M1.3-M2.8
LF060P-A ESD	Push-to-Start	145898	0.8 - 5.2	3 - 58.8	1550	1 1/2"	9"	1/4 F/Hex	15.5 oz	M1.3-M2.8
LF080-A ESD	Lever Start	145891	1.7 - 6.9	19.6 - 78.4	1250	1 1/2"	9"	1/4 F/Hex	15.5 oz	M1.7-M3
LF080P-A ESD	Push-to-Start	145892	1.7 - 6.9	19.6 - 78.4	1250	1 1/2"	9"	1/4 F/Hex	15.5 oz	M1.7-M3
LF120-A ESD	Lever Start	145893	2.6 - 10.4	29.4 - 117.6	1000	1 1/2"	9"	1/4 F/Hex	15.5 oz	M2.0-M4
LF120P-A ESD	Push-to-Start	145894	2.6 - 10.4	29.4 - 117.6	1000	1 1/2"	9"	1/4 F/Hex	15.5 oz	M2.0-M4
LF180-A ESD	Lever Start	145895	3.5 - 15.6	39.3 - 176.6	700	1 1/2"	9"	1/4 F/Hex	15.5 oz	M2.6-M4
LF180P-A ESD	Push-to-Start	145896	3.5 - 15.6	39.3 - 176.6	700	1 1/2"	9"	1/4 F/Hex	15.5 oz	M2.6-M4