



Televes reserves the right to modify the product

## NevoSwitch 9 inputs - 16 outputs

### When quality matters

Multiswitch equipped with 9 inputs (one terrestrial and 8 for two satellites, each with its four polarities) and 16 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.714603

Art.Nr

MS916C

EAN13

8424450173091

## Highlights

- 10 dB Low Gain (LG) / High Gain (HG) switch for the attenuation of the satellite input signal for each 8-user group
- Remote power feeding using VL
- Current circulation between all inputs and cascades
- Compatible with return-channel applications
- European design, quality, and manufacturing

## Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

## Technical specifications

<b>Type</b>			9x9x16
<b>Frequency range</b>	MHz	SAT	950 ... 2200 / 2400
		RF	88 ... 862
		RET	5 ... 65
<b>Input level</b>	dBμV	SAT	112
		RF	90
<b>Through losses</b>	dB	SAT	3.5 ... 7.5 / 10
		RF	4
		RET	6
<b>Tap losses</b> 1..8 / 9..16 / 17..24 / 25..32	dB	SAT(1)	0/4/-/-
		RF	4/6/-/-
		RET	34/37/-/-
<b>Isolation</b>	dB	H/V	>30
		Users	>25
<b>DCPass</b>			In-Out / Out-In
<b>Powering</b>	Vdc	PSU Trunk lines	12
		User output (STB)	12-18
<b>Max. total consump.</b>	mA	PSU Low Gain(2)	85
		PSU High Gain(2)	180
		User Output (STB)	35
<b>Protection level</b>		IP	20
<b>Temp. range</b>		°C	-5...+45

(1) LG - 10dB.

(2) if output charged --> +45mA.