



# HDMI Matrix Routing Switcher

Model: 1T-MX-6344



**1T-MX-6344 4x4 HDMI Matrix Switcher** is designed to allow distribution of four HDMI (or DVI) sources independently to four destinations. The 1T-MX-6344 supports HDMI v1.3 Deep Color (10 bit color) video and new lossless, compressed Dolby TrueHD, Dolby Digital Plus as well as DTS-HD Master Audio digital audio. HDCP is supported and all signal paths are fully buffered to prevent cross talk. Frequency bandwidth is 2.25 Gbps (Single Link) and each input signal is reconstituted into a new signal before being output thereby eliminating any jitter component.

HDTV signals up to 1080p and PC signals up to UXGA signals are supported as well as 480i and 576i SDTV. Special mechanical features include TV One's exclusive locking DC power connector as well as compatibility with locking type HDMI cable connectors. RS-232 and Infrared Remote Control are provided in addition to front panel pushbuttons. Rackmount ears are included.



### Key Features of the 1T-MX-6344

- 4x4 Matrix HDMI Matrix Routing Switcher
- HDMI v1.3 Compliant
- DVI Compatible (with DVI to HDMI Adapters)
- Full Embedded Digital Audio I/O Support
- PC Resolutions through UXGA
- HD Resolutions through 1080p
- SD Resolutions of 480i and 576i
- RS-232 Interface
- IR Remote Control
- IR Extender
- Rack Mount Kit included

### Specifications

<b>Video Inputs</b>	
HDMI (Note 1)	4x via HDMI Type A Connectors
<b>Video Outputs</b>	
HDMI (Note 1)	4x via HDMI Type A Connectors
<b>Audio Inputs/Outputs</b>	
Embedded Audio	Dolby TrueHD, Dolby Digital Plus, DTS-HD
<b>Performance</b>	
Compliance	HDMI v1.3, HDCP 1.1, DVI 1.0
Signal Processing	Compensated, Clock Phase Adjusted
Jitter Processing	Reconstituted Signal; Jitter Free
Color Processing	30 bit (10 bit/color)
Frequency Bandwidth	2.25Gbps (Single Link)
Video Resolutions	480i through 1080p, VGA through UXGA
Audio Processing	Dolby, DTS 32-192 fs sample, LPCM 7.1, all Channels
EDID	Auto or Manual Discovery
Cable Distance-Input	20m (66 ft.) (1080p/8 Bit)
Cable Distance-Output	15m (49 ft.) (1080p/8 Bit)
Control Methods	Front Panel, RS-232, IR Remote (IR Extender included)

<b>Mechanical</b>	
Size (H-W-D)	1.75"x17.2"x 6.9"(44x438x175mm)
Weight (Net)	6.8 lbs (3.1Kgs)
<b>Warranty</b>	
Limited Warranty	3 Years Parts and Labor
<b>Environmental</b>	
Operating Temp.	0° to +50°C (+32° to +122°F)
Operating Humidity	10% to 90%, Non-condensing
Storage Temperature	-10° to +60°C (+14° to +140° F)
Storage Humidity	10% to 90%, Non-condensing
<b>Power Requirement</b>	
External Power Supply	5VDC - Locking DC
<b>Regulatory Approvals</b>	
Switcher Units	FCC, CE, RoHS
Power Supplies	UL, CUL, CE, PSE, GS, RoHS
<b>Accessories Included</b>	
1x AC Power Adapter	US, UK or European Type
1x RC-44	IR Remote Control Unit
1x IR Extender	
1x Rack Mount Kit	
1x Operations Manual	
<b>Product Number</b>	
1T-MX-6344	HDMI 4x4 Matrix Switcher
<b>Notes</b>	
(1) DVI Compatible by using HDMI to DVI Adapters.	

### Panel Drawings

